

TECHNICAL AND SAFETY DATA SHEET PEST DEFENDER

1. PRODUCT AND MANUFACTURER

Trade name:	Pest Defender
Preparation date:	11/2024
Use:	Rodent control
Manufactured in Spain with Akron technology by:	Barlesa s.l. P.I. Molí d'en Fonolleda, C/ del treball, 8-10. CP 08186 Lliçà d'Amunt. Spain
Product description:	Stainless steel fibers EN 1.4113 and fire-retardant recycled polyester fibers
Weight:	1050 g/m2 +/- 10%
Thickness:	14 mm +/- 10%
Tear resistance UNE-EN ISO 13937-2	45 Newtons
Tensile strength UNE-EN ISO 13934-1	27 Newtons
Elongation UNE-EN ISO 13934-1	42%

2. COMPOSITION

Stainless steel wool fiber section:	39% = between 0.1 and 0.11 mm 35% = between 0.09 and 0.1 mm 26% = between 0.08 and 0.09 mm
Stainless steel fiber length:	From 60 to 120 mm
PES filament section:	30% 4 dtex 70% 17 dtex
PES fiber length:	70% 51 mm 30% 64 mm
Stainless steel analysis:	% C 0.03 % SI 0.34 % MN 0.93 % P 0.02 % S 0.10 % CR 16.07 % MO 0.90 % NI 0.27

3. SAFETY DATA SHEET

It is recommended to use safety glasses and cut-resistant gloves when handling the product.
Toxicological classification not applicable.